



BVCert. 6010761



EAN Code : 3543290003803

CONFIGURATION	Storing shelf	Sliding shelf	Beverage grid
Standard Configuration	5	1	1

* Traditional Bordeaux bottles

Oxygen

Range :	Oxygen
Function :	Multi-functions (2-temperatures)
Reference :	OXG2T206NVSD
Equipment :	6 shelves and one multi-drinks grid
Capacity* :	206 Bottles*



Constant and reliable temperature thanks to the wine cabinet insulation, the controller and the aluminium walls.



Humidity rate between 65% and 80% ensuring by our product design, the cooling and venting system,



The natural venting system of our wine cabinets ensures constant air renewal within the wine cabinet.



Ideal protection against UV rays thanks to our glass door with double pan reinforced with gaz argon to filter up to 97% of the UV rays.



No vibration thanks to the slow-cycles compressor fixed on silentblocs + evaporator flooded in the high density polyurethane foam.

General Features

Dimensions H x W x D (mm):	1825 x 680 x 690	Weight cabinet empty (kg) :	108
Dimensions in pack (mm) :	1950 x 720 x 760	Weight equipped cabinet (kg) :	123,60
Colors :	Black	Useful volume (L) :	445
Door:	Glass door silver frame		

Equipment & Accessories

Equipment

- Glass door with silver frame, integrated handle in the glass frame.
- Glass door with double pan reinforced with gaz argon to filter up to 97% of the UV rays.
- Lock
- Reversible door
- 2 adjustable feet
- Labels for the bottles identification

Accessories

Universal shelves: AOHU1

Code EAN : 3543290002783

Weight : 2,6

Bottles capacity per level : 12 *

Material : Solid beech wood.

Modular system : you can choose the shelf configuration :



Sliding shelf
« 12 bottles »



Presentation shelf
« 6+22 bottles »



Storing shelf
« 72 bottles »

The label holder allows you to identify your bottle quickly and easily



Suitable to store all types of bottles



Technical features

Control Panel

- Electronic regulation. From 10°C to 14°C for the ageing compartment and from 3°C to 6°C for the cooling compartment
- Inner electronic display, Red Leds screen
- Visual alarm for the temperature fault
- Temperature display
- Automatic Winter function

Performances

Cold production :	Static cooling
Hot production :	Heating element
Humidity:	Ensure by the thermodynamical pump system
Winter function:	Automatic
Gaz uses :	R600a
Recommended temperature range :	From 12°C to 25 °C
Climate class :	SN
Inner material:	Aluminium
Insulation type:	PU foam
Acoustic emissions (db(A)):	37
Consumption Aec(kWh/ An)**:	252

* Traditional Bordeaux bottles

** Comply with DEPARTMENT OF ENERGY – 10 CFR Part 430 – Energy Conservation Program: Energy Conservation Standards for Miscellaneous Refrigeration Products .Alimentation 115V 60Hz